	MINGER BIHAR.	IAR.	240	Unit.
	COR	DESCRIPTION	No.	
31.140.		(1) ROOF TREATMENT OF PH-II, BLOCK-C	Caml	
		Area of roof treatment of Ph-II, Block-C = 2921.15 Stt (2/1.46 3411)	) July	
		SECTION-I (P.C.C./R.C.C. WORK)		
	17 57	Grading roof for water proofing treatment with		
-	12.52.2	Cement concrete 1:2:4 (1 cement: 2 coarse sand: 4	27.59	Cum
		graded stone aggregate 20 mm nominal size)		-
	2 4.12	Extra for providing and mixing water proofing materi-		kg ce-
		al in cement concrete work in the proportion	174.00	ment
		recommended by the manufacturer.		
	3 14.83	14.83 Hacking of C.C. flooring including cleaning 101		
		surface etc. complete as per direction of the	271.48	8 Sqm
		Engineer-in-charge: TOTAL		
		ROUNDUP	-	-
		Cost of construction per sq. ft.		
		OF PH	•	
		(2) GOLA OF /5X/5 WIN CIVITOR = 378 X 6" = 164.00 Sft (15.24 Sqm)	00 Sft (15.24	(mpS
		n Ph-II, BIOCK-C -		
T	1 12.38	12.38 Providing gola 75x75 mm in cement concrete 1.2.4 (1		
		O		
		down gauge) including finishing with cement mortar		
		1:3(1 cement: 3 coarse sand) as per standard design.	15.24	24 Sqm
	12.38.1	In 75x75 mm deep chase		
	i i	TOTAL		

